



COSTA

Pellet stove

PERFECTION
IN EVERY WAY!



High efficiency

Modern regulation and special construction ensures high efficiency which enables rapid production of large amounts of hot air and a lot of savings.



The clean glass

Special design of the combustion chamber, multi-modulation and soft start system ensures that the glass is clean and allows long to enjoy the view of the flames.



Modern control

Multi-modulation system, soft start, night mode, ECO mode, weekly schedule and remote control in standard ensure easy and user-friendly operation.



Silent system

High quality components such as muted motor gear or cross flow blower ensure quiet operation of the stove.



bordo - RAL 3004



antracit - RAL 9005



vanilla - RAL 1015





Parametr:

Heating efficiency:
 Nominal output :
 Output with reduced power:
 Fuel consumption at nominal output:
 Width:
 Height:
 Depth:
 Exhaust outlet external diameter:
 Average exhaust temperature at nominal output:
 Average exhaust temperature at reduced output:
 Exhaust gas mass flow at nominal output:
 CO emission at nominal output (13% O₂):
 Required chimney draught:
 Noise level:
 Power supply:
 Electrical insulation:
 Electric power consumption – fans and motoreducer:
 Electric power consumption – lightener:
 Ambient temperature:
 Humidity 10-90% without condensation:

Unit:	Costa
%	85,5
kW	7,5
kW	4
kg/h	ok. 1,8
mm	500
mm	930
mm	520
mm	80
°C	190
°C	125
g/s	7
mg/m ³	233
Pa / mbar	1 ÷ 5 / 0,01 ÷ 0,05 under 75
dB	1 PEN ~50Hz 230V TN-S IP 20
W	135
W	170
°C	15 ÷ 40
%	10 ÷ 90%

HKS LAZAR Spółka z o. o.



44-335 Jastrzębie Zdrój
 ul. Wodzisławska 15B, POLAND



+48 32 47 57 123
 +48 32 47 29 578



office@hkslazar.com

